

MOBILE TRAILER MAINTENANCE

FHWA/BIT/PM - TRAILER

Perform: FHWAIPM-6 Mos. or 35,000 Miles. BIT/PM-3 Mos.			
Inspecting Company: <u>Bowman</u>		617090T	
Inspecting Company's Address: <u>ORLANDO</u>		TERA	
Trailer Number: <u>SL 61249</u>	Make: <u>WABCO</u>		
Date: <u>9.14.2026</u>	Year: <u>2024</u>		
Inspect each item and use these codes:		Refrigeration Hour Reading: Eng.() Switch ()	
		Hub Reading: <u>NA</u>	
Codes: Unsatisfactory = X Serviced = S Checked OK = ✓ Out of Service = O			
Front		Sides	
Inspect 7-way receptacle.	✓	Inspect Marker Lights.	✓
Inspect Glad Hands, rubbers.	✓	Inspect Conspicuity Tape.	✓
Inspect King Pin & Plate.	✓	Inspect Bottom and Top Rails, Sheared Rivets.	✓
Inspect Clearance Lights.	✓	Check the Hub Oil Level/Nuts on Grease Caps.	✓
Rear		Identification	
Inspect Mud Flaps & Brackets.	✓	Inspect Unit numbers front and rear	✓
Inspect Rear Door; opens and closes easily.	✓	Inspect License plate matches registration.	✓
Inspect Door hold backs for all Doors.	✓	Inspect Document box on Trailer Nose.	✓
Ramp		Inspect FHWA certificate in Document Box.	
Inspect Spring Assist.	NA	Underride Supports & Bar	
Inspect Stops, Locks, Chains & Handles.	NA	Steps, Anti-Slip Dock Bumpers.	
General		Inside (if Empty)	
Lubricate Landing Gear.	✓	Inspect Walls for Kemlite Damage.	
Inspect Sand Shoes; Flat.	✓	Inspect Scuff Liner, E-Trac, Pallet Stops.	
Inspect Bracing for legs.	✓	Inspect Bulkheads, Air Chute.	
Blow out Drain Hoses.	NA	Egress and Ingress	
Sub Frame		Inspect all Grab Handles, Steps & Platforms.	
Inspect Rails and Crossmembers.	✓	Lubricate all Doors, Door Hinges.	
Inspect Springs, Hangars, Saddles & U-bolts.	✓	Lubricate Roll Up Door, Rollers, Hinges & Latch.	
Inspect Equalizers, Radius Rods & Bushings.	✓	Brakes	
Tires		Air Leaks, Valve Operation.	
Inspect Rims, no cracks.	✓	Inspect Brake Lining.	
Inspect Tires for irregular wear.	✓	Lubricate Cams & Slack Adjuster Zerks	
Inspect Tires, inflate to 100 p.s.i.	✓	Adjust Brakes.	
Tread Depth in 32nds		Inspect Brake Chamber.	
LFO: <u>11</u>	RFO: <u>15</u>	Brake Pad Thickness in 32nds	
LFI: <u>11</u>	RFI: <u>4</u>	LF: <u>12</u>	RF: <u>12</u>
LRO: <u>8</u>	RRO: <u>14</u>	LR: <u>10</u>	RR: <u>10</u>
LRI: <u>8</u>	RRI: <u>16</u>		
Comments:			
Certification: This vehicle has passed all the inspection items for the annual vehicle inspection report in accordance with 49 CFR 396.			
Your Signature: <u>Alan Miller</u>		Print Name: <u>Alan Miller</u>	