

## Van Trailer Annual Checklist

California/6-month Inspection

SRT = 1.0 hour

Unit Number 0725F Date 3/26/15 Work Order \_\_\_\_\_ Location OR

0725F

<input type="checkbox"/> Satisfactory <input checked="" type="checkbox"/> Defective <input checked="" type="checkbox"/> Corrected		Detail Line
<b>Front Section</b>		
✓	1	Verify PM due/Check TBO's/chock wheels/install lock-out tag
✓	2	Light plug (connect lights) inspect lights
✓	3	Glad-hands/Hoses/Connect to air supply (don't apply service brakes) release emergency brakes. Adjust glad hands so they lay flat against the trailer with the ends turned downward slightly so that water cannot enter it.
✓	4	Manifest box and bag/Placard holder/Body/Decals/Registration/Data plate
✓	5	Coupler/king pin
✓	6	Cycle Props two rotations up and down in high and low gear. Inspect Handle/Brackets/Legs/Cross frame/mounting bolts. Grease props legs. Lubricate ratcheting crank handles.
<b>Roadside</b>		
✓	7	Placard holder/Body/Rail damage/Decals/Reflective tape/door holdback chain
✓	8	Grease mid-ship and beehive Marker lights/Turn lights
✓	9	Lug nuts/Hubcaps/Hubcap bolts
✓	10	Flats/Tread depth/Air & equalize tires to 100 PSI /Jackson Tire Gauge
✓	11	Slider Pins/Slider Rails/Gussets/Spring hangers/Equalizer/Slider Handle Operation EZ pull handle stop & decal present
✓	12	Mud flaps/Brackets
<b>Rear Section</b>		
✓	13	ICC Bumper/Door hardware (security hardware)/Doors/Door seal
✓	14	Placard holder/License plate and hardware/Decals/Reflective tape
✓	15	Empty Trailer Only - Close Doors - Interior leaks/Door seals (light check)
<b>Curbside</b>		
✓	16	Placard holder/Body/Rail damage/Decals/Reflective tape/door holdback chain
✓	17	Grease mid-ship and beehive Marker lights/Turn lights
✓	18	Lug nuts/Hubcap bolts/Hubcaps
✓	19	Flat/Tread depth/Air & equalize tires to 100 PSI /Jackson Tire Gauge
✓	20	Slider Pins/Slider Rails/Gussets/Spring hangers/Equalizer
✓	21	Mud flaps/Brackets
<b>Undercarriage</b>		
✓	22	Springs/Hangers/U-Bolts/Radius rods/Paint push rods
✓	23	Valves/Hoses/Tanks/Air line springs
✓	24	Wheel seals/Max's/S-Cams/Brackets/Slacks/Shoe condition/Drums/ Refer to SB 13-93 for brake chamber inspection details.
✓	25	Grease cam bushings & slacks (brakes must be released). Use Mag#2 (chassis grease). Lube slack adjuster clevis pins.
✓	26	Emergency application spring (spring brake) remove inspection plug /
✓	27	Verify no danger of cam-over before next PM
<b>Roof</b>		
✓	28	Roof/Rivets/Holes
<b>Finish</b>		
✓	29	Apply service brakes/Air leaks/Stroke/
✓	30	PM decal/Update M5/update TBO screen/charge out parts

Qualified Inspector Signature *Ray Mays* Mechanic Number \_\_\_\_\_

This inspection meets annual inspection requirements of FWHA 49 CFR Part 396 Appendix G

Updated 12/19/2012 - Replaces 10/29/2012

\* Right Rear wheel seal pump but not blown, Bowman said let it go.