

SH

Record of Annual Inspection



The Inspector of this vehicle meets the qualification requirements contracted in D.O.T. rule 49 CFR section 396.19

10233 Governor Lane Blvd
P.O. Box 433 Williamsport, MD 21795-0733

F - (301) 223-7674
P - (800) 635-6733

Unit #: 376040
MFG/Year: 5/2004
Date of Inspection: 6/3/2005

Serial #: S791575
Date of Inspection: 6/3/2005
(Month/Day/Year)

Inspection Location: Bowman/Boxer
(Branch ID, City & State)

Registration valid installed in Registration Holder.

License Plate # VA22185 State VA Expiration: 1/92

All Marker, Clearance, Stop/Turn, Flashers and License Plate Lights are operational. All Electric Harnesses are secured properly. Seven way plug properly secured.

All Front and side panels are free of holes or damage. Top and bottom rails, front top rails and lower rails are free of damage, properly fastened to cross members, posts and panels.

ICC assembly is properly secured, step is secure and functional and has reflective tape installed. Tailights are functioning properly; rear doors close and lock properly and have reflective tape installed top and bottom. Mud flaps and brackets are installed and secure.

Air Ride Suspension - Spring Ride Suspension Springs, Rebound bolts, U-Bolts, Equalizers, Radius Rods, are free of damage, excessive wear, secure and free of defects. Air bags are intact, shocks are properly installed, free of excessive oil and leaks, brackets are attached and secure.

Slider Rails are properly secured to the cross members, no gaps or broken welds. Slider Pins are properly installed and engaged to the slider rails. Slider handle is properly secured. OEM Gussets are intact. Landing Gear straight, braces intact, properly attached to Wing Plate and Cross Members handle in good condition and able to be properly secured.

All Glad Hand Grommets are free of tears and excessive wear. Glad hands are properly secured to the front Panel/bulkhead; Airlines are secured by a slider return spring. All airlines are free of wear marks, chaffing and defects. Air tanks are properly secured and drained.

Brake adjustment checked, brake thickness measured, slack adjusters properly secured and operational. Manual or Auto Slack equipped. Spring brakes are not caged, are free of excessive rust and Corrosion. Brake Drums are intact, no excess wear or damage, free of oil and grease.

Front axle brake thickness Rear axle Brake Thickness

Optional equipment is functional (Lift Gate), batteries secured properly. Winches & straps properly secured And in good condition.

Tires matched (within 6/32nds tread depth), free of dry rot, cuts cord or belt exposure, properly inflated. All lug nuts properly secured, rims are free of cracks, damage, or excessive wear with no oil present on rims. All hubs are in good condition with proper fluid levels.

TREAD DEPTH 32/100"

POSITION

LBS

Radial = R

Radial Recap = RRC

Radial = R

Radial = R

Radial = R

Radial = R

TREAD DEPTH	POSITION	LBS	POSITION	LBS	TREAD DEPTH	POSITION	LBS	POSITION	LBS
6	8	100	6	100	6	8	100	6	100
8	8	100	6	100	8	8	100	6	100
10	10	100	10	100	10	10	100	10	100
10	10	100	10	100	10	10	100	10	100

Radial = R

Radial = R

Radial = R

Radial = R

Radial = R

Radial = R

Radial = R

Radial = R

Radial = R

Radial = R

Radial = R

Radial = R

Radial = R